


NEOTEC



Roller Blind Applications

COLOUR RANGE



White



Stable



Linen white




White Sable




Chalk



Linen




Fog



Ochre




Mink



Bark



Midnight



Granite




Iron



Soot



Jewel



Alpine Haze



Royal

Note: Colours are as accurate as the printing process allows

NEOTEC

Soltec the level of glare entering your home.

Available in a wide range of colours, Neotec's modern 2 x 2 basket weave design provides a consistent look throughout the home.

Features & Benefits

PVC Coated Polyester

Sunscreens can let in natural light whilst reducing the level of glare, they are particularly good in situations where computer screens are used.

2 x 2 Basket Weave

Modern design which provides a consistent weave look.

17 Colours

Modern colour range designed to suit most Australian interiors.

Light Filtering

The unique weave allows light to filter and provide a certain level of daytime privacy.

UV Resistant

All colours meet Australian Standards for colour fastness to resist fading.

Tested for harmful substance

Neotec fabric meets the certification requirements set by Oeko-Tex for the exclusion of harmful substances.

GREENGUARD®

Neotec fabric meets the certification requirements set by GREENGUARD® for low chemical emissions.

Technical Specifications

Composition

PVC coated Polyester

Fabric Weight

420 gsm ± 5%

Fabric Thickness

0.55mm ± 5%

Colour Fastness

5-7 Blue Scale

Openness Factor

5% average (dependent on colour)

Breaking Strength

1700n ± 225n

Tearing Strength

66n ± 10n

Care and Cleaning

General Care

Remove dust with vacuum cleaner on low suction setting. Do not scrub.

Stains

Clean with sponge dipped in soapy water. Leave blind down until completely dry.

Solar Optical Guide

SOLAR OPTICAL PROPERTIES

COLOUR	HEAT PROPERTIES			VISIBLE LIGHT PROPERTIES		
	TS	RS	AS	TL	TUV	SC
White	20	66	14	12	4	0.34
Linen White	19	56	25	13	6	0.41
Sable	14	55	31	9	4	0.41
Chalk	24	63	13	18	6	0.37
Linen	16	51	33	11	5	0.44
Midnight	5	5	90	6	5	0.73
Bark	5	6	89	6	5	0.72
Iron	6	16	78	6	5	0.66
Granite	6	11	83	6	5	0.69
Alpine Haze	12	44	44	9	5	0.48
Jewel	14	49	37	10	5	0.45
Sable	22	59	19	21	6	0.40
Fog	18	53	34	9	5	0.44
Ochre	8	22	70	10	6	0.62
Royal	6	16	78	6	5	0.65
Soot	9	32	59	7	5	0.56
Mink	5	9	86	5	4	0.70

The solar optical properties listed above have been tested by Matrix, Inc. an independent solar laboratory based in Arizona, USA

Solar Optical Properties Guide

TS	Heat Transmittance (%)
RS	Heat Reflectance (%)
AS	Heat Absorbance (%)
TL	Light Transmittance (%)
TUV	Ultraviolet Transmittance (%)
SC	Shading Coefficient (%)

Ignitability Index* 0
[Range 0-10]

Spread of Flame Index* 0
[Range 0-10]

Heat Evolved Index* 0
[Range 0-10]

Smoke Developed Index* 5
[Range 0-10]

Fire Retardant INFORMATION

Neotec Fabric has a Fire Retardancy rating suitable for residential applications. It has been independently tested to AS1530.3* and AS1530.2*.